

PSAL® 38S SLIM LINE NITROGEN GENERATOR N2

SKIT PLATTFORMEN - ÜBERSICHT

Skit Plattform	Volume flow - Nm³/h 3.0 (99,9%) / 4.0 (99,99%) / 5.0 (99,999%)	Platform dimensions LxWxH in mm	Platform weight (approx. in kg)	Power connection
PSAL 38S SLIM LINE	38 / 22 / 11	2200x2200x2500	2580	32A

SPECIFICATIONS / DATA

- Outlet pressure max. 300 bar
- Ambient air +4°C to +45°C
- Nitrogen purity 3.0 = 1000ppm
- Highest purity 5.0 = 10ppm
- Nitrogen temperature +10°C above ambient temperature

BENEFITS

- Plug'N'Play
- Immediately operational
- Low maintenance effort
- High quality & worldwide service
- Air requirement factor 5-7
- Purity at 3.0 - 5.0

HIGHLIGHTS

- Small footprint and easy handling
- Extremely low power consumption
- Extremely low air consumption
- Delivery quantity and purity expandable with N-Kat Kit
- Better cutting results than tank and bundle solutions
- Industry 4.0, query & control of the system from anywhere in the world



DOWNLOAD PDF

High pressure
compressor

